STEEL SHIM STOCK

DMR Steel Shim is low carbon mild steel cold rolled to a #1 hard temper. It is stiff and springy, and can be used where hardness is required. The material can be punched or sheared with minimum burring and distortion. Steel Shim Stock meets the following specifications: AISI 1010 & QQS 698. Available in .001" to .031" and in standard packages 6" X 100" or 12" X 120". Special slit widths are also available on request. Typical weight .010" X 6" X 100" = 1.7lbs.

6" X 100" ROLLS

THICKNESS	DMR PART #
.001	30001-001
.0015	30805-015
.002	30002-002
.003	30003-003
.004	30004-004
.005	30005-005
.006	30006-006
.007	30007-007
.008	30008-008
.009	30009-009
.010	30010-010
.012	30012-012
.015	30015-015
.020	30020-020
.025	30025-025
.031	30031-031

12" X 120" ROLLS

THICKNESS	DMR PART #
.001	32001-001
.002	32002-002
.003	32003-003
.004	32004-004
.005	32005-005
.006	32006-006
.007	32007-007
.008	32008-008
.009	32009-009
.010	32010-010
.012	32012-012
.015	32015-015
.018	32018-018
.020	32020-020
.025	32025-025
.031	32031-031

STEEL SHIM TOLERANCES

Decimal Thickness	6" Width	12" Width
.001-.003 .0035 - .006 .007 - .018	+/- 10% +/- .005 +/- .00075	+/- 10% +/- .005 +/- .00075
.020 -.025 .031	+/- .001 +/- .0015	+/- .001 +/- .0015
Width Tolerance	+/- .005	+/- .010