


# ASC Series Threaded Aluminum Caps for Threaded Flared Fittings



A standard aerospace and fluid power protective cap, Series ASC has a nose-section design that forms a low-pressure seal on threaded flared fittings. A more positive seal is possible with the addition of a sealing disc (Series ASC-DN). Stock sealing discs are Neoprene; Butyl or Buna N rubber are also available.

**Material:** 3003-0 Aluminum Alloy **Color:** Natural (Silver)

**Applicable Specs:** MIL-C-5501/3, NAS-817, NAS-835



Caplug No.	Dimensions						Packaging	
	To Fit Tube Size	To Fit Thread Size	A		B		Carton Quantity	Mini Pak Quantity
			In	mm	In	mm		
ASC-2	1/8	5/16-24	.42	10.67	.33	9.65	5000	1000
ASC-3	3/16	3/8-24	.36	9.14	.30	7.62	5000	1000
ASC-4	1/4	7/16-20	.54	13.72	.46	11.68	5000	1000
ASC-5	5/16	1/2-20	.52	13.21	.43	10.92	5000	1000
ASC-6	3/8	9/16-18	.54	13.72	.46	11.68	6000	1000
ASC-7	7/16	5/8-18	.61	15.49	.52	13.21	5000	1000
ASC-8	1/2	3/4-16	.64	16.26	.55	13.97	6000	1000
ASC-10	5/8	7/8-14	.74	18.80	.65	16.51	3700	500
ASC-12	3/4	1-1/16-12	.85	21.59	.76	19.30	2200	500
ASC-16	1	1-5/16-12	.86	21.84	.76	19.30	1400	200
ASC-20	1-1/4	1-5/8-12	.87	22.22	.71	18.25	950	190

\* For other material and color options, contact a Daemar Sales Representative.